

**LIGHTENNING  
ARRESTER**

---

## LIGHTNING PROTECTORS

### MODEL NAME *MSG-NPNP6G-23*

<b>FREQUENCY</b>	0~6.0GHz
<b>CONNECTOR</b>	N Plug to N Plug
<b>IMPEDANCE</b>	50 ohms
<b>VSWR</b>	≤1.5:1
<b>VOLTAGE</b>	DC 230V±20%
<b>INSERTION LOSS</b>	0.1dB/1GHz, 0.2dB/2GHz, 0.4dB/3GHz, 0.5dB/4GHz, 0.6dB/6GHz
<b>POWER(@25 °C)</b>	250W/300MHz, 160W/500MHz, 100W/900MHz, 75W/1.2GHz, 52W/1.9GHz, 42W/2.4GHz, 36W/3GHz, 10W/6GHz
<b>WORKING TEMP.</b>	-30°C ~ +85°C



### MODEL NAME *MSG-NJNSJ6G-23*

<b>FREQUENCY</b>	0~6.0GHz
<b>CONNECTOR</b>	N Jack to N Jack
<b>IMPEDANCE</b>	50 ohms
<b>VSWR</b>	≤1.5:1
<b>VOLTAGE</b>	DC 230V±20%
<b>INSERTION LOSS</b>	0.1dB/1GHz, 0.2dB/2GHz, 0.4dB/3GHz, 0.5dB/4GHz, 0.6dB/6GHz
<b>POWER(@25 °C)</b>	250W/300MHz, 160W/500MHz, 100W/900MHz, 75W/1.2GHz, 52W/1.9GHz, 42W/2.4GHz, 36W/3GHz, 10W/6GHz
<b>WORKING TEMP.</b>	-30°C ~ +85°C



### MODEL NAME *MSG-NJNP6G-20*

<b>FREQUENCY</b>	0~6.0GHz
<b>CONNECTOR</b>	N Jack to N Plug
<b>IMPEDANCE</b>	50 ohms
<b>VSWR</b>	≤1.5:1
<b>VOLTAGE</b>	DC 230V±20%
<b>INSERTION LOSS</b>	0.1dB/1GHz, 0.2dB/2GHz, 0.4dB/3GHz, 0.5dB/4GHz, 0.6dB/6GHz
<b>POWER(@25 °C)</b>	250W/300MHz, 160W/500MHz, 100W/900MHz, 75W/1.2GHz, 52W/1.9GHz, 42W/2.4GHz, 36W/3GHz, 10W/6GHz
<b>WORKING TEMP.</b>	-30°C ~ +85°C



NOTE: SOME SIZES, STYLES AND OPTIONS ARE NON-STANDARD, NON-CANCELLABLE AND NON-RETURNABLE.

## LIGHTNING PROTECTORS

### MODEL NAME *MSG-SRPJSRPP6G-23*

<b>FREQUENCY</b>	0~6.0GHz
<b>CONNECTOR</b>	RP SMA Jack to RP SMA Plug
<b>IMPEDANCE</b>	50 ohms
<b>VSWR</b>	≤1.5:1
<b>VOLTAGE</b>	DC 230V±20%
<b>INSERTION LOSS</b>	0.1dB/1GHz, 0.2dB/2GHz, 0.4dB/3GHz, 0.5dB/4GHz, 0.6dB/6GHz
<b>POWER(@25 ° C)</b>	250W/300MHz, 160W/500MHz, 100W/900MHz, 75W/1.2GHz, 52W/1.9GHz, 42W/2.4GHz, 36W/3GHz, 10W/6GHz
<b>WORKING TEMP.</b>	-30°C ~ +85°C



### MODEL NAME *MSG-TRPJTRPP6G-23*

<b>FREQUENCY</b>	0~6.0GHz
<b>CONNECTOR</b>	RP TNC Jack to RP TNC Plug
<b>IMPEDANCE</b>	50 ohms
<b>VSWR</b>	≤1.5:1
<b>VOLTAGE</b>	DC 230V±20%
<b>INSERTION LOSS</b>	0.1dB/1GHz, 0.2dB/2GHz, 0.4dB/3GHz, 0.5dB/4GHz, 0.6dB/6GHz
<b>POWER(@25 ° C)</b>	250W/300MHz, 160W/500MHz, 100W/900MHz, 75W/1.2GHz, 52W/1.9GHz, 42W/2.4GHz, 36W/3GHz, 10W/6GHz
<b>WORKING TEMP.</b>	-30°C ~ +85°C



NOTE: SOME SIZES, STYLES AND OPTIONS ARE NON-STANDARD, NON-CANCELLABLE AND NON-RETURNABLE.